

Timken

H249148/H249111CD+H249148XB tapered roller bearings

Enjoy High Margins on Competitive Pricing.Great Wholesale Products at 381×546.1×104.775 Size (mm) Low Costs.

| | |
|-------------------------------|-------------------|
| Size (mm) | 381×546.1×104.775 |
| Bore Diameter (mm) | 381 |
| Outer Diameter (mm) | 546,1 |
| Width (mm) | 104,775 |
| d | 381 mm |
| D | 546,1 mm |
| T | 104,775 mm |
| B | 104,775 mm |
| C | 82,55 mm |
| R | 6,3 mm |
| r | 6,3 mm |
| a – | 7,1 mm |
| Da | 520 mm |
| db | 417 mm |
| da | 407 mm |
| Db | 507 mm |
| Aa | 9,1 mm |
| Ab | 5,4 mm |
| Weight | 75,13 Kg |
| Basic static load rating (C0) | 4210 kN |
| Factor (G1) | 4383,4 |

| | |
|----------------------------------|---------|
| Factor (G2) | 278,7 |
| Factor (Cg) | 0,0682 |
| Factor (K) | 1,76 |
| Basic dynamic load rating (C90) | 502 |
| Basic dynamic load rating (Ca90) | 286 |
| Basic dynamic load rating (C1) | 1940 kN |
| Calculation factor (e) | 0,33 |