

Timken HH221434/HH221410-B tapered roller bearings

Question Timken HH221434/HH221410-B tapered roller bearings ?
Find 440 Bore Diameter (mm) what you 440x650x196 Size (mm)
need faster by entering your 650 Outer Diameter (mm)
information .

| | |
|-------------------------------|-------------|
| Size (mm) | 440x650x196 |
| Bore Diameter (mm) | 440 |
| Outer Diameter (mm) | 650 |
| Width (mm) | 196 |
| d | 440 mm |
| D | 650 mm |
| T | 196 mm |
| C | 157 mm |
| r min. | 6 mm |
| r1 min. | 3 mm |
| da min. | 468 mm |
| Da min | 620 mm |
| ra max. | 5 mm |
| rb max. | 2,5 mm |
| Weight | 198 Kg |
| Basic dynamic load rating (C) | 3000 kN |
| Basic static load rating (C0) | 6370 kN |
| (Grease) Lubrication Speed | 300 r/min |
| (Oil) Lubrication Speed | 400 r/min |
| Calculation factor (e) | 0,39 |
| Calculation factor (Y0) | 1,7 |

| | |
|--------------------|--------|
| Bearing No. | 46288A |
| r(min) | 6 |
| r1(min) | 3 |
| Cr | 3770 |
| C0r | 6370 |
| Cu | 300 |
| Grease lub. | 300 |
| Oil lub. | 400 |
| da(min) | 468 |
| Da(min) | 636 |
| Sa(min) | 19.5 |
| ra(max) | 5 |
| rb(max) | 2.5 |
| e | 0.39 |
| Y2 | 1.74 |
| Y3 | 2.59 |
| Y0 | 1.70 |
| (Refer.) Mass (kg) | 198 |