

# Timken HH923649/HH923610 tapered roller bearings

What is 600 Outer Diameter (mm) the best place to buy Timken HH923649/HH923610 tapered roller bearings 400x600x200 Size (mm) online? 400 Bore Diameter (mm) Manufacturing Service .

Size (mm)	400x600x200
Bore Diameter (mm)	400
Outer Diameter (mm)	600
Width (mm)	200
d	400 mm
D	600 mm
B	200 mm
C	200 mm
r min.	5 mm
da min.	422 mm
Da max.	578 mm
ra max.	4 mm
Weight	200 Kg
Basic dynamic load rating (C)	3 850 kN
Basic static load rating (C0)	8 400 kN
(Grease) Lubrication Speed	460 r/min
(Oil) Lubrication Speed	600 r/min
Calculation factor (e)	0,32
Calculation factor (Y0)	2,04
Calculation factor (Y1)	2,09
D1	527.7 mm
rs min	5 mm

Number of lubrication holes	8
b	27 mm
k	16 mm
e	0.32
Y1	2.09
Y2	3.11
Y0	2.04
Radial clearance class	CN
Dynamic load, C	3,850 kN
Static load, C0	8,400 kN
Fatigue limit load, Cu	630 kN
Nref	520 rpm
Nlim	1,000 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0 Hz
Characteristic rolling element frequency, BSF	0 Hz
Characteristic outer ring frequency, BPF0	0 Hz
Characteristic inner ring frequency, BRFI	0 Hz
da min	418 mm
Da max	582 mm
ra max	4 mm