

# Timken HM237532/HM237510 tapered roller bearings

100% Authentic. N/A Minimum Buy Quantity Timken HM237532/HM237510 tapered roller bearings Highest Quality. Certified Supplier. 0.0 Inventory

Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight	0.631
Product Group	B00152
Enclosure	2 Metal Shields
Flush Ground	No
Rolling Element	Ball Bearing
Number of Rows of Balls	Double Row
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Steel
Contact Angle	25 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Inch – Metric	Metric
Long Description	40MM Bore; 80MM Outside Diameter; 30.2MM Width; 2 Metal Shields; No Flush Ground; Ball Bearing; Doub
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28

Noun	Bearing
Keyword String	Angular Contact
Manufacturer Item Number	5208CZZ
B	1.189 Inch   30.2 Millimeter
D	3.15 Inch   80 Millimeter
d	1.575 Inch   40 Millimeter
bore diameter:	40 mm
radial static load capacity:	29000 N
outside diameter:	80 mm
operating temperature range:	-40 to 120 °C
overall width:	1.1875 in
cage material:	Steel
contact angle:	25 °
outer ring width:	30.2 mm
row type & fill slot:	Double-Row Non-Fill Slot
maximum rpm:	7100 RPM
internal clearance:	C0
finish/coating:	Uncoated
bore type:	Round
precision rating:	Class 0
closure type:	Double Shield
fillet radius:	1.1 mm
snap ring included:	Without Snap Ring
series:	52
bearing material:	High Carbon Chrome Steel
weight:	0.631 kg
radial dynamic load capacity:	36500 N
manufacturer product page:	<a href="#">Click here</a>