

Timken HM813844/HM813815-B tapered roller bearings

Find the discount Timken HM813844/HM813815-B tapered roller bearings 47 Bore Diameter (mm) online you need . We offer ... If you check out our large selection of Timken HM813844/HM813815-B tapered roller bearings once . 47×19.05×31 Size (mm)

Size (mm)	47×19.05×31
Bore Diameter (mm)	47
Outer Diameter (mm)	19,05
Width (mm)	31
d	19.05 mm
A	32 mm
H	64 mm
H1	33,3 mm
L	60,3 mm
C0 – Static load	6,55 kN
Weight	0,5 kg
Grub (set) screw – – 10-32×1/4	1032×1/4
Size hexagonal key	3,175 mm
A1	24,61 mm
J	89,7 mm
T	32,6 mm
D	47 mm
B	31 mm
C	14 mm
d1	28.2 mm
B4	4.5 mm

s1	18.3 mm
r1,2 – min.	0.6 mm
Basic dynamic load rating – C	12.7 kN
Basic static load rating – C0	6.6 kN
Limiting speed	270 r/min
Limiting temperature – T	350 °C
Mass bearing	0.17 kg
Grub (set) screw – G2 – 1/4-28 UNF	1/428 UNF
Hexagonal key size for grub screw – H	3.175 mm
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.14
EAN	7316572167434
Product Group	M06110
Inner Race Profile	Wide Inner Ring
Outer Race Profile	Spherical
Relubricatable	No
Seal Type	M Seal
Mounting Method	Set Screw
Rolling Element	Ball Bearing
Snap Ring	No
Long Description	3/4" Bore; Wide Inner Ring; Ball Bearing; 1.221" Length Thru Bore; 0.551" Outer Race
Inch – Metric	Inch

Other Features	Single Row Standard Duty Grub Screw Hi-Temp Bearing With Graphite Technology Has Flinger
UNSPSC	31171536
Harmonized Tariff Code	8482.10.50.00
Noun	Bearing
Keyword String	Insert
Manufacturer Item Number	YAR 204-012-2FW/VA228
Weight / LBS	0.309
Bore	0.75 Inch 19.05 Millimeter
Outer Race Width	0.551 Inch 13.995 Millimeter
Length Thru Bore	1.221 Inch 31.013 Millimeter
Outside Diameter	1.85 Inch 46.99 Millimeter
bore diameter:	0.7500 in
radial static load capacity:	6.55 kN
outside diameter:	47 mm
bearing material:	Stainless Steel
outer ring width:	14 mm
finish/coating:	Zinc Plated
inner ring width:	31 mm
maximum rpm:	270 RPM
bore type:	Round
seal type:	Contact with Flinger
locking device:	Set Screw
series:	YAR2
operating temperature range:	-240 to +660 °F
d1 ≈	28.2 mm

r1,2 min.	0.6 mm
Basic dynamic load rating C	12.7 kN
Basic static load rating C0	6.55 kN
Limiting temperature T max.	350 °C
Grub (set) screw G2	1/4-28 UNF
Hexagonal key size for grub screw N	3.175 mm
Recommended tightening torque for grub screw	4 N·m