

# Timken JM714249A/JM714210 tapered roller bearings

Timken JM714249A/JM714210 tapered roller bearings  
 Manufacturers N/A Minimum Buy Quantity , Online Wholesale 0.0  
 Inventory Suppliers ☐ !

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | REGAL BELOIT   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 4.313  |
| EAN                       | 0662461018545  |
| Product Group             | M06110   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Set Screw  |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Ball Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 5/8 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 3-111DC  |
| Seals                     | Single Lip Contact   |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Single Row   Medium Duty   Has Flinger   With Set Screw                                    |
| Long Description          | 2 Bolt Pillow Block; 1-11/16" Bore; 2-3/8" Base to Center Height; Set Screw Mount; Ball Be |

|                               |                                |
|-------------------------------|--------------------------------|
| UNSPSC                        | 31171511                       |
| Harmonized Tariff Code        | 8483.20.40.40                  |
| Noun                          | Bearing                        |
| Keyword String                | Pillow Block                   |
| Manufacturer Item Number      | MSPD-27C                       |
| Manufacturer Internal Number  | 702564                         |
| Weight / LBS                  | 9.5                            |
| Bolt Spacing Minimum          | 6.438 Inch   163.525Millimeter |
| Nominal Bolt Center to Center | 6.9 Inch   175.3 Millimeter    |
| Bolt Spacing Maximum          | 7.438 Inch   188.925Millimeter |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter           |
| d                             | 1.688 Inch   42.875 Millimeter |
| B                             | 2.375 Inch   60.325 Millimeter |
| D                             | 2.5 Inch   63.5 Millimeter     |