

Timken K45X53X20FH,ZB2 needle roller bearings

Shop Timken K45X53X20FH,ZB2 needle roller bearings 0.0 Inventory huge online discount inventory. and Import machinery parts your car N/A Minimum Buy Quantity needs with Free Shipping and Free Extended Warranty.

| | |
|---------------------------------|---|
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 0.09 |
| EAN | 7316570020939 |
| Product Group | B00308 |
| Enclosure | 2 Seals |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Enclosure Type | Contact Seal |
| Internal Clearance | C0-Medium |
| Inch – Metric | Metric |
| Long Description | 12MM Bore; 37MM Outside Diameter; 17MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; |
| Other Features | Cartridge Bearing |
| UNSPSC | 31171504 |

| | |
|--------------------------|----------------------------|
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer Item Number | 62301-2RS1 |
| Weight / LBS | 0.198 |
| D | 37 mm |
| d | 12 mm |
| Outer Race Width | 0.669 Inch 17 Millimeter |
| bore diameter: | 12 mm |
| static load capacity: | 4.15 kN |
| outside diameter: | 37 mm |
| precision rating: | Not Rated |
| overall width: | 17 mm |
| finish/coating: | Uncoated |
| bore type: | Round |
| outer ring width: | 17 mm |
| closure type: | Double Sealed |
| fillet radius: | 1 mm |
| row type & fill slot: | Single Row Non-Fill Slot |
| maximum rpm: | 14000 RPM |
| internal clearance: | C0 |
| series: | 62 |
| dynamic load capacity: | 9.75 kN |
| B | 17 mm |
| d1 ≈ | 19.5 mm |
| D2 ≈ | 31.48 mm |
| r1,2 min. | 1 mm |
| da min. | 17.6 mm |
| da max. | 19.4 mm |

| | |
|-----------------------------|-------------|
| Da max. | 31.4 mm |
| ra max. | 1 mm |
| Basic dynamic load rating C | 9.75 kN |
| Basic static load rating C0 | 4.15 kN |
| Fatigue load limit Pu | 0.176 kN |
| Limiting speed | 14000 r/min |
| Calculation factor kr | 0.03 |
| Calculation factor f0 | 11 |
| Mass bearing | 0.07 kg |