Timken LL382149/LL382110 tapered roller bearings

170 Million used Timken LL382149/LL382110 tapered roller bearings instantly searchable. Shop our large selection of Exceptional Bearing Protection, Rotating Applications, Pumps, Gearboxes, Motors, Energy Efficient Ap typical application: parts based on brand, price, description, and 3.4828 in shaft diameter: location. Order the with stock ...

shaft diameter: Rypical application: Exceptional Bearing Protection, Rotating Applications, Pumps, Gearboxes, Motors, Energy Efficient Ap Labyrinth harmonization code: Syzegou4590.US ISO-GARD® Flangeless Design, Filled PTFE Rotor and Stator, FKM O-Rings manufacturer catalog number: 29519-6609 continuous temperature range: -22 to 400°F Weight 0.24 lb maximum shaft surface speed: 4500 fpm D 4.5060 in misalignment tolerance: 0.020 in width: pressure tolerance: Ambient		
typical application: Rotating Applications, Pumps, Gearboxes, Motors, Energy Efficient Ap lip material: Labyrinth harmonization code: 3926904590.US ISO-GARD® Flangeless Design, Filled PTFE Rotor and Stator, FKM O-Rings manufacturer catalog number: 29519-6609 continuous temperature range: -22 to 400°F Weight 0.24 lb maximum shaft surface speed: 4500 fpm D 4.5060 in misalignment tolerance: 0.020 in width:	shaft diameter:	3.4828 in
harmonization code: 3926904590.US ISO-GARD® Flangeless Design, Filled PTFE Rotor and Stator, FKM O-Rings manufacturer catalog number: 29519-6609 continuous temperature range: -22 to 400°F Weight 0.24 lb maximum shaft surface speed: 4500 fpm D 4.5060 in misalignment tolerance: 0.020 in width: 0.6250 in	typical application:	Rotating Applications, Pumps, Gearboxes, Motors, Energy
ISO-GARD® Flangeless Design, Filled PTFE Rotor and Stator, FKM O-Rings manufacturer catalog number: 29519-6609 continuous temperature range: -22 to 400°F Weight 0.24 lb maximum shaft surface speed: 4500 fpm D 4.5060 in misalignment tolerance: 0.020 in width: 0.6250 in	lip material:	Labyrinth
construction description: Filled PTFE Rotor and Stator, FKM 0-Rings manufacturer catalog number: 29519-6609 continuous temperature range: -22 to 400°F Weight 0.24 lb maximum shaft surface speed: 4500 fpm D 4.5060 in misalignment tolerance: 0.020 in width: 0.6250 in	harmonization code:	3926904590.US
continuous temperature range: -22 to 400°F Weight 0.24 lb maximum shaft surface speed: 4500 fpm D 4.5060 in misalignment tolerance: 0.020 in width: 0.6250 in	construction description:	Filled PTFE Rotor and Stator,
Weight 0.24 lb maximum shaft surface speed: 4500 fpm D 4.5060 in misalignment tolerance: 0.020 in width: 0.6250 in	manufacturer catalog number:	29519-6609
maximum shaft surface speed: 4500 fpm D	continuous temperature range:	-22 to 400°F
D 4.5060 in misalignment tolerance: 0.020 in width: 0.6250 in	Weight	0.24 lb
misalignment tolerance: 0.020 in width: 0.6250 in	maximum shaft surface speed:	4500 fpm
width: 0.6250 in	D	4.5060 in
	misalignment tolerance:	0.020 in
pressure tolerance: Ambient	width:	0.6250 in
	pressure tolerance:	Ambient