

Timken LL420549/LL420510 tapered roller bearings

Timken LL420549/LL420510 tapered roller bearings with easy-to-use parts graphics, giving you the ability to 150 Outer Diameter (mm) check 100x150x37 Size (mm) parts availability, pricing, examine remanufactured options.

| | |
|---------------------|------------|
| Size (mm) | 100x150x37 |
| Bore Diameter (mm) | 100 |
| Outer Diameter (mm) | 150 |
| Width (mm) | 37 |
| d | 100 mm |
| D | 150 mm |
| B | 37 mm |
| C | 37 mm |
| d1 | 115 mm |
| r1 min. | 1,5 mm |
| r2 min. | 1,5 mm |
| r3 min. | 1 mm |
| r4 min. | 1 mm |
| D1 | 134 mm |
| E | 139,65 mm |
| da min. | 107 mm |
| Da max. | 142 mm |
| das rec. | 112 mm |
| ra max. | 1,5 mm |
| rb max. | 1 mm |
| S | 4 mm |

| | |
|-------------------------------|------------|
| Db max | 143 mm |
| Weight | 2,15 Kg |
| Basic dynamic load rating (C) | 209 kN |
| Basic static load rating (C0) | 310 kN |
| Fatigue load limit (Pu) | 37,5 |
| Reference speed | 2000 r/min |
| Limiting speed | 2600 r/min |