

Timken

M268749/M268710CD+M268749XE tapered roller bearings

High Quality Timken M268749/M268710CD+M268749XE tapered roller bearings. Competitive 76,2 Bore Diameter (mm) Pricing. Accept Small Order. Easy and 76.2×136.525×30.162 Size (mm) Fast Shipping.

Size (mm)	76.2×136.525×30.162
Bore Diameter (mm)	76,2
Outer Diameter (mm)	136,525
Width (mm)	30,162
d	76,2 mm
D	136,525 mm
T	30,162 mm
B	29,769 mm
C	22,225 mm
a	29,8 mm
r min.	3,6 mm
r2 min.	3,2 mm
da min.	92 mm
Da	122 mm
db min	86 mm
ra max.	3,6 mm
rb max.	3,2 mm
Db	130 mm
Weight	1,804 Kg
Basic dynamic load rating (C)	133 kN

Basic static load rating (C0)	198 kN
(Grease) Lubrication Speed	2700 r/min
(Oil) Lubrication Speed	3600 r/min
Calculation factor (e)	0,44
Calculation factor (Y0)	0,74
Bearing No.	495A/493
r(min)	3.6
r1(min)	3.2
Cr	167
C0r	198
Cu	30.0
Grease lub.	2700
Oil lub.	3600
a(mm)	29.8
da	92.0
db	86.0
ra(max)	3.6
rb(max)	3.2
e	0.44
Y1	1.35
Y0	0.74
(Refer.) Mass (kg)	1.80