

# Timken N207KLL deep groove ball bearings

Request A Quote For 0.0 Inventory Your TIMKEN Manufacturer Name Special Timken N207KLL deep groove ball bearings Needs Today! Free Quotes. ISO 9001 certified.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 7.718  |
| EAN                       | 0883450189866                                  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | Concentric Collar                              |
| Housing Style             | 4 Bolt Pillow Block                            |
| Rolling Element           | Spherical Roller Bearing                       |
| Housing Material          | Cast Steel                                     |
| Expansion / Non-expansion | Expansion                                      |
| Mounting Bolts            | 5/8 Inch                                       |
| Relubricatable            | Yes  |
| Insert Part Number        | 22213  |
| Seals                     | Triple Lip Nitrile Rubber                      |
| Housing Configuration     | 1 Piece Solid                                  |
| Inch – Metric             | Inch   |
| Other Features            | Double Row   Single Collar  <br>With Set Screw |

|                               |  |
|-------------------------------|--|
| Long Description              | 4 Bolt Pillow Block; 2-1/2" Bore; 2-3/4" Base to Center Height; Concentric Collar Mount; S |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.80  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Manufacturer Item Number      | QAPR13A208SEM  |
| Weight / LBS                  | 20   |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter   |
| D                             | 3.39 Inch   86.106 Millimeter  |
| B                             | 2.75 Inch   69.85 Millimeter   |
| Bolt Spacing Minimum          | 7.125 Inch   180.975Millimeter   |
| d                             | 2.5 Inch   63.5 Millimeter   |
| Nominal Bolt Center to Center | 7.9 Inch   199.5 Millimeter  |
| Bolt Spacing Maximum          | 8.75 Inch   222.25Millimeter   |