

Timken RNA2110 needle roller bearings

YOU'LL FIND AN 228.6 mm da EXTENSIVE SELECTION 107.798 mm Ca OF Timken RNA2110 needle roller bearings FOR 359.999 mm Da SALE.

da	228.6 mm
Da	359.999 mm
Ca	107.798 mm
A1	203.2 mm
A2	285.75 mm
ba	89.694 mm
H	422.275 mm
H1	209.55 mm
H2	85.725 mm
J min.	571.5 mm
J max.	635 mm
J1	127 mm
L	749.3 mm
N1	34.925 mm
R1	122.237 mm
R2	42.862 mm
RG	1 NPT
PG	1/4 NPT
h	56.356 mm
Housing	SAF 048 KA
Bearing	23048 CCK/W33
Adapter sleeve assembly	SNP 3048×9

Stabilizing ring	2 x A8897
Labyrinth ring	2 x LOR 513
PosiTrac Plus contact element	2 x B10724-552
End plug (suffix Y)	X-5217-4
Max. speed for PosiTrac Plus seal	640 r/min
P60°	364 kN
P90°	218 kN
P120°	136 kN
P150°	120 kN
P180°	145 kN
Pa	66.7 kN
Mass pillow block	181 kg
Cap bolt	4 x 7/8-9 UNC
Cap bolt recommended tightening torque	271.2 N·m
Cap bolt, SAE grade	5
Eye bolt	2 x 1/2-13 UNC
Appropriate attachment bolt size G	1.25 in
Initial grease fill	2154.6 g