

Timken RNA2110 needle roller bearings

YOU'LL FIND AN 228.6 mm da EXTENSIVE SELECTION 107.798 mm Ca OF Timken RNA2110 needle roller bearings FOR 359.999 mm Da SALE.

| | |
|-------------------------|---------------|
| da | 228.6 mm |
| Da | 359.999 mm |
| Ca | 107.798 mm |
| A1 | 203.2 mm |
| A2 | 285.75 mm |
| ba | 89.694 mm |
| H | 422.275 mm |
| H1 | 209.55 mm |
| H2 | 85.725 mm |
| J min. | 571.5 mm |
| J max. | 635 mm |
| J1 | 127 mm |
| L | 749.3 mm |
| N1 | 34.925 mm |
| R1 | 122.237 mm |
| R2 | 42.862 mm |
| RG | 1 NPT |
| PG | 1/4 NPT |
| h | 56.356 mm |
| Housing | SAF 048 KA |
| Bearing | 23048 CCK/W33 |
| Adapter sleeve assembly | SNP 3048×9 |

| | |
|--|----------------|
| Stabilizing ring | 2 x A8897 |
| Labyrinth ring | 2 x LOR 513 |
| PosiTrac Plus contact element | 2 x B10724-552 |
| End plug (suffix Y) | X-5217-4 |
| Max. speed for PosiTrac Plus seal | 640 r/min |
| P60° | 364 kN |
| P90° | 218 kN |
| P120° | 136 kN |
| P150° | 120 kN |
| P180° | 145 kN |
| Pa | 66.7 kN |
| Mass pillow block | 181 kg |
| Cap bolt | 4 x 7/8-9 UNC |
| Cap bolt recommended tightening torque | 271.2 N·m |
| Cap bolt, SAE grade | 5 |
| Eye bolt | 2 x 1/2-13 UNC |
| Appropriate attachment bolt size G | 1.25 in |
| Initial grease fill | 2154.6 g |