

# Timken RNA017X25X20 needle roller bearings

Timken RNA017X25X20 needle roller bearings Deal 0.0 Inventory is your source for OEM and NTN Manufacturer Name accessories. We sell Genuine at discount prices.

|                      |   |
|----------------------|---|
| Inventory            | 0.0                                       |
| Manufacturer Name    | NTN                                       |
| Minimum Buy Quantity | N/A                                       |
| Weight               | 0.37                                      |
| EAN                  | 4547359030686                             |
| Product Group        | B04270                                    |
| Enclosure            | Open                                      |
| Precision Class      | ABEC 9   ISO P2                           |
| Material – Ball      | Steel                                     |
| Number of Bearings   | 2 (1 Pair)                                |
| Contact Angle        | 15 Degree                                 |
| Preload              | Light                                     |
| Raceway Style        | 1 Rib Inner Ring                          |
| Cage Material        | Phenolic                                  |
| Rolling Element      | Ball Bearing                              |
| Mounting Arrangement | Duplex-Back to Back                       |
| Flush Ground         | Yes                                       |
| Inch – Metric        | Metric                                    |
| Other Features       | Single Row   Angular Contact   High Speed |

|                               |   |
|-------------------------------|---|
| Long Description              | 40MM Bore; 68MM Outside Diameter; 30MM Width; Open Enclosure; ABEC 9   ISO P2 Precision; Steel Ball |
| UNSPSC                        | 31171531  |
| Harmonized Tariff Code        | 8482.10.50.28   |
| Noun                          | Bearing   |
| Keyword String                | Angular Contact Ball  |
| Manufacturer Item Number      | BNT008DB/GNP2   |
| Weight / LBS                  | 0.816   |
| d                             | 1.575 Inch   40 Millimeter  |
| D                             | 2.677 Inch   68 Millimeter  |
| B                             | 1.181 Inch   30 Millimeter  |
| bore diameter:                | 40 mm   |
| precision rating:             | ISO Class 2   |
| outside diameter:             | 68 mm   |
| cage material:                | Phenolic Resin  |
| overall width:                | 30 mm   |
| finish/coating:               | Uncoated  |
| contact angle:                | 15 °  |
| inner ring width:             | 15 mm   |
| duplex type:                  | Tandem  |
| maximum rpm (oil):            | 18000 rpm   |
| closure type:                 | Open  |
| maximum rpm (grease):         | 14000 rpm   |
| operating temperature range:  | -40 to 120 °C   |
| outer ring width:             | 15 mm   |
| radial dynamic load capacity: | 25500 N   |
| fillet radius:                | 1 mm  |
| radial static load capacity:  | 20800 N   |

|                            |                            |
|----------------------------|----------------------------|
| manufacturer product page: | <a href="#">Click here</a> |
| bearing material:          | High Carbon Chrome Steel   |