

# Timken RNA020X32X24 needle roller bearings

170 Million used Timken RNA020X32X24 needle roller bearings instantly searchable. Shop our 0.0 Inventory large selection of parts based on TIMKEN Manufacturer Name brand, price, description, and location. Order the with stock ...

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 4.994  |
| EAN                       | 0883450028271                                  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Concentric Collar                              |
| Housing Style             | 2 Bolt Pillow Block                            |
| Rolling Element           | Spherical Roller Bearing                       |
| Housing Material          | Cast Steel                                     |
| Expansion / Non-expansion | Non-expansion                                  |
| Mounting Bolts            | 5/8 Inch                                       |
| Relubricatable            | Yes  |
| Insert Part Number        | 22210  |
| Seals                     | Triple Lip Viton                               |
| Housing Configuration     | 1 Piece Solid                                  |
| Inch – Metric             | Inch   |
| Other Features            | Double Row   Double Collar  <br>With Set Screw |

|                               |  |
|-------------------------------|--|
| Long Description              | 2 Bolt Pillow Block; 1-15/16" Bore; 2-1/4" Base to Center Height; Concentric Collar Mount; |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.80  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Manufacturer Item Number      | QAAPL10A115SN  |
| Weight / LBS                  | 13   |
| d                             | 1.938 Inch   49.225 Millimeter   |
| Bolt Spacing Minimum          | 5.93 Inch   150.622Millimeter  |
| Bolt Spacing Maximum          | 6.36 Inch   161.544Millimeter  |
| D                             | 3.78 Inch   96 Millimeter  |
| Nominal Bolt Center to Center | 6.3 Inch   160 Millimeter  |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter   |
| B                             | 2.25 Inch   57.15 Millimeter   |