

# Timken SM1008K deep groove ball bearings

offers a Timken SM1008K deep groove ball bearings selection of Genuine at Wholesale Prices. We are a Timken SM1008K deep groove ball bearings Certified Parts 0.0 Inventory Retailer

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | ASAHI BEARINGS  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 0.63  |
| EAN                       | 0808250156245   |
| Product Group             | M06110  |
| Number of Mounting Holes  | 4   |
| Mounting Method           | Set Screw   |
| Housing Style             | 4 Bolt Square Flange Block  |
| Rolling Element           | Ball Bearing  |
| Housing Material          | Cast Iron   |
| Expansion / Non-expansion | Non-expansion   |
| Mounting Bolts            | 10 Millimeter   |
| Relubricatable            | Yes   |
| Insert Part Number        | UC202C4HR23   |
| Seals                     | Contact Seal  |
| Housing Configuration     | 1 Piece Solid   |
| Pilot Configuration       | No Pilot  |
| Inch – Metric             | Metric  |
| Long Description          | 4 Bolt Square Flange Block;<br>15MM Bore; 90.5MM Bolt Circle;<br>64MM Bolt Spacing; 1 Piece<br>Solid; Set Scr |

|                                    |  |
|------------------------------------|--|
| Other Features                     | Single Row   Spherical   Normal Duty   High Temperature Range Up to 450 Degree F   Has Slinger |
| UNSPSC                             | 31171501   |
| Harmonized Tariff Code             | 8483.20.40.40  |
| Noun                               | Bearing  |
| Keyword String                     | Flanged  |
| Manufacturer Item Number           | UCF202C4HR23   |
| Weight / LBS                       | 1.38   |
| Cartridge Pilot Depth              | 0 Inch   0 Millimeter  |
| Cartridge Pilot Diameter           | 0 Inch   0 Millimeter  |
| D                                  | 1.22 Inch   31 Millimeter  |
| Nominal Bolt Circle Diameter Round | 3.6 Inch   90.5 Millimeter   |
| Bolt Spacing                       | 2.52 Inch   64 Millimeter  |
| d                                  | 0.591 Inch   15 Millimeter   |