

# Tower Crane Excavator Slewing Ring Bearing Manufacture China

Welcome to 9,000 Bore Diameter (mm) the Tower Crane Excavator Slewing Ring Bearing Manufacture China online seller. 9x13x3 Size (mm)

Size (mm)	9x13x3
Bore Diameter (mm)	9,000
Outer Diameter (mm)	13,000
Width (mm)	3,000
d	9,000 mm
D	13,000 mm
B	3,000 mm
C	3,000 mm
rs min	0.1 mm
Radial clearance class	CN
Mass	0.002 kg
Dynamic load, C	0.92 kN
Static load, C0	0.46 kN
Fatigue limit load, Cu	0.02 kN
f0	15.5
Nlim (oil)	42,000 rpm
Nlim (grease)	36,000 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
da min	9.8 mm

Da max	13.2 mm
ra max	0.1 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.001
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Stainless Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	9MM Bore; 14MM Outside Diameter; 3MM Outer Race Width; Open; Ball Bearing; ABEC 1   ISO P0; No Filli
Other Features	Deep Groove   Stainless Steel Ring and Ball
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.002
Outside Diameter	0.551 Inch   14 Millimeter
Bore	0.354 Inch   9 Millimeter
Inner Race Width	0 Inch   0 Millimeter

Outer Race Width	0.118 Inch   3 Millimeter
------------------	---------------------------