

Toyana 21075/21212 tapered roller bearings

How do I 40 mm d place an EMERGENCY order for a Toyana 21075/21212 tapered roller bearings that I want to pick 80 mm D up at a our store?

d	40 mm
D	80 mm
B	18 mm
E	71.5 mm
F	49.5 mm
d1	53.9 mm
rs min	1.1 mm
rls min	1.1 mm
Radial clearance class	C3
Mass (without HJ ring)	0.38 kg
Dynamic load, C	55.5 kN
Static load, C0	55.5 kN
Fatigue limit load, Cu	6.8 kN
Nlim (oil)	10,000 rpm
Nlim (grease)	8,500 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	5.32 Hz
Characteristic outer ring frequency, BPF0	5.73 Hz

Characteristic inner ring frequency, BPI	8.27 Hz
da min	46.5 mm
dc min	56 mm
Da max	73.5 mm
ra max	1 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.385
EAN	4547359134414
Product Group	B04144
bore diameter:	40 mm
precision rating:	Not Rated
outside diameter:	80 mm
maximum rpm:	10000 RPM
overall width:	18 mm
bearing material:	High Speed Steel
flanges:	(4) Flanges, Two-Piece Inner Ring
cage material:	Plastic
bore type:	Straight
finish/coating:	Uncoated
number of rows:	1
closure type:	Open
internal clearance:	C3
outer ring width:	18 mm
ring separation:	Non-Separable
fillet radius:	1 mm

dynamic load capacity:	5700 kgf
series:	NUP
static load capacity:	5650 kgf