

Toyana 22217 MBW33 spherical roller bearings

What are 71.438 mm da the types of Toyana 22217 MBW33 spherical roller bearings ? Manufacturing Service . Get Your Free, Instant price, design review.

| | |
|---------|------------|
| da | 71.438 mm |
| Da | 150 mm |
| Ca | 45.796 mm |
| A1 | 88.9 mm |
| A2 | 127 mm |
| S | 4.763 mm |
| ba | 35.719 mm |
| H | 187.325 mm |
| H1 | 95.25 mm |
| H2 | 38.1 mm |
| J min. | 250.825 mm |
| J max. | 279.4 mm |
| J1 | 53.975 mm |
| L | 330.2 mm |
| N1 | 19.05 mm |
| R1 | 53.975 mm |
| R2 | 22.225 mm |
| RG | 3/8 NPT |
| PG | 1/8 NPT |
| h | 34.925 mm |
| Housing | FSAFS 517 |
| Bearing | 22217 EK |

| | |
|--|----------------|
| Adapter sleeve assembly | SNW 17×2.13/16 |
| Stabilizing ring | SR-17-14 |
| Labyrinth ring | 2 x LOR 51 |
| End plug (suffix Y) | EPR 9 |
| Bearing limiting speed | 5600 r/min |
| P60° | 83.2 kN |
| P90° | 49.8 kN |
| P120° | 31.6 kN |
| P150° | 28.5 kN |
| P180° | 33.8 kN |
| Pa | 9.25 kN |
| Mass pillow block | 24.5 kg |
| Cap bolt | 2 x 5/8-11 UNC |
| Cap bolt recommended tightening torque | 298.3 N·m |
| Cap bolt, SAE grade | 8 |
| Appropriate attachment bolt size G | 0.625 in |
| Initial grease fill | 110.56 g |