

Toyana 22224 MBW33 spherical roller bearings

Toyana 22224 MBW33 spherical roller bearings SEARCH – 40x44x40 Size (mm) Whether it's agriculture or construction equipment your working on, Has the you need.

| | |
|-------------------------------|---------------|
| Size (mm) | 40x44x40 |
| Bore Diameter (mm) | 40 |
| Outer Diameter (mm) | 44 |
| Width (mm) | 40 |
| d | 40 mm |
| D | 44 mm |
| B | 40 mm |
| c1 min | 0,1 mm |
| c2 min | 0,8 mm |
| M | – mm |
| Weight | 0,078 Kg |
| Basic dynamic load rating (C) | 125 kN |
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.88 |
| EAN | 7316571886039 |
| Product Group | B04264 |
| c1 min. | 0.1 mm |
| c1 max. | 0.7 mm |
| c2 min. | 0.8 mm |
| c2 max. | 1.6 mm |

| | |
|--|-----------------------|
| $\alpha \pm 8$ | 20 ° |
| Tolerance shaft | f7 |
| Tolerance housing | H7 |
| Basic dynamic load rating – radial direction C | 125 kN |
| Basic static load rating – radial direction C0 | 390 kN |
| Specific dynamic load factor K | 80 N/mm ² |
| Specific static load factor K0 | 250 N/mm ² |
| Factor depending on material and bearing type KM | 480 |
| Permissible sliding velocity v min. | 0 m/s |
| Permissible sliding velocity v max. | 2 m/s |
| Coefficient of friction μ min. | 0.03 |
| Coefficient of friction μ max. | 0.25 |
| Mass bushing | 0.078 kg |