

Toyana 22232 KW33+H3132 spherical roller bearings

Enjoy High Margins on Competitive Pricing.Great 68 Bore Diameter (mm) Wholesale Products 68x40x15 Size (mm) at Low 40 Outer Diameter (mm) Costs.

| | |
|-------------------------------|------------|
| Size (mm) | 68x40x15 |
| Bore Diameter (mm) | 68 |
| Outer Diameter (mm) | 40 |
| Width (mm) | 15 |
| d | 40 mm |
| D | 68 mm |
| B | 15 mm |
| d1 | 49.2 mm |
| D2 | 62.5 mm |
| r1,2 – min. | 1 mm |
| da – min. | 45 mm |
| da – max. | 49 mm |
| Da – max. | 63.5 mm |
| ra – max. | 1 mm |
| Basic dynamic load rating – C | 14.6 kN |
| Basic static load rating – C0 | 11.4 kN |
| Fatigue load limit – Pu | 0.49 kN |
| Limiting speed | 6300 r/min |
| Calculation factor – kr | 0.03 |
| Calculation factor – f0 | 15.2 |
| Inventory | 0.0 |
| Manufacturer Name | SKF |

| | |
|---------------------------------|---|
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.175 |
| EAN | 7316570648621 |
| Product Group | B00308 |
| Enclosure | 2 Seals |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Stainless Steel |
| Enclosure Type | Contact Seal |
| Internal Clearance | C0-Medium |
| Inch – Metric | Metric |
| Long Description | 40MM Bore; 68MM Outside Diameter; 15MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No |
| Other Features | Deep Groove NBR Seal |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer Item Number | W 6008-2RS1 |
| Weight / LBS | 0.4916 |
| Outside Diameter | 2.677 Inch 68 Millimeter |
| Inner Race Width | 0 Inch 0 Millimeter |
| Bore | 1.575 Inch 40 Millimeter |
| Outer Race Width | 0.591 Inch 15 Millimeter |
| d1 ≈ | 49.2 mm |

| | |
|---|---------|
| D2 ≈ | 62.5 mm |
| r _{1,2} min. | 1 mm |
| d _a min. | 45 mm |
| d _a max. | 49 mm |
| D _a max. | 63.5 mm |
| r _a max. | 1 mm |
| Basic dynamic load rating C | 14.6 kN |
| Basic static load rating C ₀ | 11.4 kN |
| Fatigue load limit P _u | 0.49 kN |
| Calculation factor k _r | 0.03 |
| Calculation factor f ₀ | 15.2 |
| Mass bearing | 0.18 kg |