

Toyana 22232 KW33+H3132 spherical roller bearings

Enjoy High Margins on Competitive Pricing.Great 68 Bore Diameter (mm) Wholesale Products 68x40x15 Size (mm) at Low 40 Outer Diameter (mm) Costs.

Size (mm)	68x40x15
Bore Diameter (mm)	68
Outer Diameter (mm)	40
Width (mm)	15
d	40 mm
D	68 mm
B	15 mm
d1	49.2 mm
D2	62.5 mm
r1,2 – min.	1 mm
da – min.	45 mm
da – max.	49 mm
Da – max.	63.5 mm
ra – max.	1 mm
Basic dynamic load rating – C	14.6 kN
Basic static load rating – C0	11.4 kN
Fatigue load limit – Pu	0.49 kN
Limiting speed	6300 r/min
Calculation factor – kr	0.03
Calculation factor – f0	15.2
Inventory	0.0
Manufacturer Name	SKF

Minimum Buy Quantity	N/A
Weight / Kilogram	0.175
EAN	7316570648621
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Stainless Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	40MM Bore; 68MM Outside Diameter; 15MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No
Other Features	Deep Groove NBR Seal
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	W 6008-2RS1
Weight / LBS	0.4916
Outside Diameter	2.677 Inch 68 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Bore	1.575 Inch 40 Millimeter
Outer Race Width	0.591 Inch 15 Millimeter
d1 ≈	49.2 mm

D2 ≈	62.5 mm
r _{1,2} min.	1 mm
d _a min.	45 mm
d _a max.	49 mm
D _a max.	63.5 mm
r _a max.	1 mm
Basic dynamic load rating C	14.6 kN
Basic static load rating C ₀	11.4 kN
Fatigue load limit P _u	0.49 kN
Calculation factor k _r	0.03
Calculation factor f ₀	15.2
Mass bearing	0.18 kg