

# Toyana 22334 ACMAW33 spherical roller bearings

Various 0.0 Inventory types and sizes TIMKEN Manufacturer Name to accommodate your Toyana 22334 ACMAW33 spherical roller bearings requirements.

|                           |                                                                                  |
|---------------------------|----------------------------------------------------------------------------------|
| Inventory                 | 0.0                                                                              |
| Manufacturer Name         | TIMKEN                                                                           |
| Minimum Buy Quantity      | N/A                                                                              |
| Weight                    | 4.03                                                                             |
| EAN                       | 0087796060210                                                                    |
| Product Group             | M06110                                                                           |
| Number of Mounting Holes  | 2                                                                                |
| Mounting Method           | Eccentric Collar                                                                 |
| Housing Style             | 2 Bolt Pillow Block                                                              |
| Rolling Element           | Ball Bearing                                                                     |
| Housing Material          | Cast Iron                                                                        |
| Expansion / Non-expansion | Non-expansion                                                                    |
| Mounting Bolts            | 1/2 Inch                                                                         |
| Relubricatable            | Yes                                                                              |
| Insert Part Number        | G1112KRRB                                                                        |
| Seals                     | Double Land Riding Rubber Contact                                                |
| Housing Configuration     | 1 Piece Solid                                                                    |
| Inch – Metric             | Inch                                                                             |
| Other Features            | Single Row   Spherical   Medium Duty   Heavy Housing   Low Base   With Set Screw |

|                               |                                                                                            |
|-------------------------------|--------------------------------------------------------------------------------------------|
| Long Description              | 2 Bolt Pillow Block; 1-3/4" Bore; 2-5/16" Base to Center Height; Eccentric Collar Mount; B |
| UNSPSC                        | 31171511                                                                                   |
| Harmonized Tariff Code        | 8483.20.40.40                                                                              |
| Noun                          | Bearing                                                                                    |
| Keyword String                | Pillow Block                                                                               |
| Manufacturer Item Number      | RAKH 1 3/4                                                                                 |
| Weight / LBS                  | 8.88                                                                                       |
| Bolt Spacing Maximum          | 0 Inch   0Millimeter                                                                       |
| d                             | 1.75 Inch   44.45 Millimeter                                                               |
| Nominal Bolt Center to Center | 6.1 Inch   156 Millimeter                                                                  |
| Actual Bolt Center to Center  | 6.1 Inch   154.9Millimeter                                                                 |
| Bolt Spacing Minimum          | 0 Inch   0Millimeter                                                                       |
| B                             | 2.313 Inch   58.75 Millimeter                                                              |
| D                             | 2.219 Inch   56.363 Millimeter                                                             |