

# Toyana 23076 KCW33 spherical roller bearings

What is the best place to buy Toyana 23076 KCW33 spherical roller bearings online? Manufacturing 40 mm d Service .

d	40 mm
D	90 mm
B	23 mm
E	80 mm
F	52 mm
d1	57.6 mm
rs min	1.5 mm
r1s min	1.5 mm
Radial clearance class	C3
Mass (without HJ ring)	0.73 kg
Dynamic load, C	83 kN
Static load, C0	81.5 kN
Fatigue limit load, Cu	9.9 kN
Nlim (oil)	8,500 rpm
Nlim (grease)	7,200 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.39 Hz
Characteristic rolling element frequency, BSF	4.5 Hz
Characteristic outer ring frequency, BPF0	4.73 Hz

Characteristic inner ring frequency, BPI	7.27 Hz
da min	48 mm
da max	51 mm
dc min	60 mm
Da max	82 mm
ra max	1.5 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.708
EAN	4547359490947
Product Group	B04144
Bore Profile	Straight
Cage Material	Brass
Precision Class	RBEC 1   ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring – One Side
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C3-Loose
Retainer	Yes
Relubricatable	Yes
Inch – Metric	Metric
Other Features	High Capacity   1 Rib Inner Ring   2 Rib Outer Ring   Cage on Outer Ring ID

Long Description	40MM Bore; Straight Bore Profile; 90MM Outside Diameter; 23MM Width; Brass Cage Material; RBEC 1
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer Item Number	NJ308EG1C3
Weight / LBS	1.565
Outside Diameter	3.543 Inch   90 Millimeter
Width	0.906 Inch   23 Millimeter
Bore	1.575 Inch   40 Millimeter
bore diameter:	40 mm
static load capacity:	81500 N
outside diameter:	90 mm
precision rating:	ISO Class 0
overall width:	23 mm
maximum rpm:	8500 rpm
flanges:	(2) Outer Ring, (1) Inner Ring
bearing material:	Hardened Alloy Steel
bore type:	Straight
cage material:	High Strength Machined Brass Rivetless w/ square holes
number of rows:	1
finish/coating:	Uncoated
internal clearance:	C3
closure type:	Open
operating temperature range:	-40 to 120 °C

fillet radius:	1.5 mm
dynamic load capacity:	83000 N
manufacturer product page:	<a href="#">Click here</a>