

Toyana 234416 MSP thrust ball bearings

Toyana 234416 MSP thrust ball bearings 104.775 mm da manufacturer and global supplier of reliable ball and roller ... Toyana 234416 MSP thrust ball bearings Industries Products Manufacturing & Engineering and Agricultural Bearings designed to meet the 215.001 mm Da unique requirements of our targeted industries.

| | |
|--------|------------|
| da | 104.775 mm |
| Da | 215.001 mm |
| Ca | 85.801 mm |
| A1 | 120.65 mm |
| A2 | 254 mm |
| S | 4.763 mm |
| ba | 61.913 mm |
| H | 257.175 mm |
| H1 | 133.35 mm |
| H2 | 53.975 mm |
| J min. | 336.55 mm |
| J max. | 368.3 mm |
| J1 | 69.85 mm |
| L | 419.1 mm |
| N1 | 22.225 mm |
| R1 | 77.787 mm |
| R2 | 30.163 mm |
| RG | 1/2 NPT |
| PG | 1/4 NPT |
| h | 46.831 mm |

| | |
|--|---------------|
| Housing | SAW 524 |
| Bearing | 23224 CCK/W33 |
| Adapter sleeve assembly | SNW 124×4.1/8 |
| Stabilizing ring | SR-24-20 |
| Taconite seal | TER 112 |
| End plug (suffix Y) | EPR 14 |
| Max. speed for Taconite seal | 750 r/min |
| P60° | 185 kN |
| P90° | 111 kN |
| P120° | 72.5 kN |
| P150° | 66.7 kN |
| P180° | 81.4 kN |
| Pa | 27.4 kN |
| Mass pillow block | 49.9 kg |
| Cap bolt | 2 x 1-8 UNC |
| Cap bolt recommended tightening torque | 400 N·m |
| Cap bolt, SAE grade | 5 |
| Appropriate attachment bolt size G | 0.75 in |
| Initial grease fill | 379.89 g |