

# Toyana 239/1000 KCW33 spherical roller bearings

We Provide Extensive 0.0 Inventory REGAL BELOIT Manufacturer Name Toyana 239/1000 KCW33 spherical roller bearings Selection And Competitive Wholesale Pricing.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | REGAL BELOIT   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 10.76  |
| EAN                       | 0662461366714  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Concentric Collar  |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Expansion  |
| Mounting Bolts            | 3/4 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | USI5000-300-C  |
| Seals                     | Double Lip Contact   |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Double Row   With Set Screw  |
| Long Description          | 2 Bolt Pillow Block; 3" Bore; 3-1/4" Base to Center Height; Concentric Collar Mount; Spher |

|                               |                                |
|-------------------------------|--------------------------------|
| UNSPSC                        | 31171511                       |
| Harmonized Tariff Code        | 8483.20.40.80                  |
| Noun                          | Bearing                        |
| Keyword String                | Pillow Block                   |
| Manufacturer Item Number      | USRB5000E-300-C                |
| Manufacturer Internal Number  | 737117                         |
| Weight / LBS                  | 23.7                           |
| Bolt Spacing Minimum          | 7.813 Inch   198.44Millimeter  |
| B                             | 3.25 Inch   82.55 Millimeter   |
| D                             | 3.875 Inch   98.425 Millimeter |
| d                             | 3 Inch   76.2 Millimeter       |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter           |
| Nominal Bolt Center to Center | 8.1 Inch   206.4 Millimeter    |
| Bolt Spacing Maximum          | 8.438 Inch   214.325Millimeter |