

Toyana 241/670 K30 CW33 spherical roller bearings

Toyana 241/670 K30 CW33 spherical roller bearings SEARCH – Whether it's agriculture or construction equipment your working 45 mm da on, Has the you need.

da	45 mm
db	53.975 mm
dc	42.875 mm
Da	100 mm
Ca	45.796 mm
A1	69.85 mm
A2	180.975 mm
S	4.763 mm
ba	30.956 mm
H	134.938 mm
H1	69.85 mm
H2	25.4 mm
J min.	187.325 mm
J max.	200.025 mm
L	244.475 mm
N1	19.05 mm
R1	38.1 mm
R2	17.462 mm
RG	1/8 NPT
PG	1/8 NPT
h	32.544 mm
Housing	SAF 309

Bearing	22309 E
Lock nut	N 09
Lock washer	W 09
Stabilizing ring	SR-11-9
Taconite seal (db shaft position)	TER 28
Taconite seal (dc shaft position)	TER 20
End plug (suffix Y)	EPR 4
Max. speed for Taconite seal	1450 r/min
P60°	35.1 kN
P90°	20.9 kN
P120°	13.3 kN
P150°	12 kN
P180°	14.7 kN
Pa	9.34 kN
Mass pillow block	8.62 kg
Cap bolt	2 x 1/2-13 UNC
Cap bolt recommended tightening torque	149.1 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.625 in
Initial grease fill	39.69 g