

# Toyana 30206 A tapered roller bearings

How do I place an EMERGENCY order 139.7 mm da for a Toyana 30206 A tapered roller bearings that I want to pick up at a our store?

da	139.7 mm
Da	289.999 mm
Ca	113.817 mm
A1	158.75 mm
A2	223.838 mm
S	4.763 mm
ba	82.55 mm
H	336.55 mm
H1	169.875 mm
H2	66.675 mm
J min.	441.325 mm
J max.	488.95 mm
J1	95.25 mm
L	558.8 mm
N1	28.575 mm
R1	104.775 mm
R2	33.337 mm
RG	3/4 NPT
PG	1/4 NPT
h	52.388 mm
Housing	SAW 532
Bearing	23232 CCK/W33

Adapter sleeve assembly	SNW 132×5.1/2
Stabilizing ring	SR-32-0
Labyrinth ring	2 x LOR 131
End plug (suffix Y)	EPR 16
Bearing limiting speed	2200 r/min
P60°	226 kN
P90°	136 kN
P120°	85.9 kN
P150°	78.3 kN
P180°	94.3 kN
Pa	49.8 kN
Mass pillow block	109 kg
Cap bolt	4 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N·m
Cap bolt, SAE grade	5
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	793.8 g