

Toyana 32215 A tapered roller bearings

LET OUR Toyana 32215 A tapered roller bearings EXPERTS GET YOU THE PARTS YOU NEED. 130x75x25 Size (mm)

Size (mm)	130x75x25
Bore Diameter (mm)	130
Outer Diameter (mm)	75
Width (mm)	25
d	75 mm
D	130 mm
B	25 mm
d1	92.05 mm
D2	116.5 mm
r1,2 – min.	1.5 mm
da – min.	84 mm
Da – max.	121 mm
ra – max.	1.5 mm
Basic dynamic load rating – C	68.9 kN
Basic static load rating – C0	49 kN
Fatigue load limit – Pu	2 kN
Reference speed	10000 r/min
Limiting speed	6700 r/min
Calculation factor – kr	0.025
Calculation factor – f0	14.7
Inventory	5.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A

Weight / Kilogram	1.21
EAN	7316577094377
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	75MM Bore; 130MM Outside Diameter; 25MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6215
Weight / LBS	2.66
Outer Race Width	0.984 Inch 25 Millimeter
Outside Diameter	5.118 Inch 130 Millimeter
Bore	2.953 Inch 75 Millimeter
d1 ≈	92.05 mm
D2 ≈	116.5 mm
r1,2 min.	1.5 mm
da min.	84 mm
Da max.	121 mm

ra max.	1.5 mm
Basic dynamic load rating C	68.9 kN
Basic static load rating C0	49 kN
Fatigue load limit Pu	2.04 kN
Calculation factor kr	0.025
Calculation factor f0	14.7
Mass bearing	1.19 kg