

Toyana 33221 A tapered roller bearings

Enjoy High Margins on Competitive 65x120x23 Size (mm) 120 Outer Diameter (mm) Pricing.Great Wholesale Products at Low Costs.

| | |
|-------------------------------|------------------|
| Size (mm) | 65x120x23 |
| Bore Diameter (mm) | 65 |
| Outer Diameter (mm) | 120 |
| Width (mm) | 23 |
| d | 65 mm |
| D | 120 mm |
| B | 23 mm |
| C | 23 mm |
| Angle (α) | 30 ° |
| a | 15.2 mm |
| r min. | 1.5 mm |
| r1 min. | 1 mm |
| 2B | 46 mm |
| da min. | 70 mm |
| Da max. | 114.6 mm |
| ra max. | 1 mm |
| Weight | 1.02 Kg |
| Basic dynamic load rating (C) | 114 kN |
| Basic static load rating (C0) | 116 kN |
| (Grease) Lubrication Speed | 3900 r/min |
| Bore Type | Cylindrical Bore |
| Enclosure | Open |

| | |
|-------------------------|-----------|
| Configuration | Duplex |
| Bore Size | 65 mm |
| Outside Diameter | 120 mm |
| Width | 23 mm |
| Fillet Radius/Chamfer | 1.5 mm |
| r1 | 1 mm |
| Dynamic Load Rating | 114,000 N |
| Static Load Rating | 116,000 N |
| Limiting Speed – Grease | 3,900 rpm |
| Limiting Speed – Oil | 5,300 rpm |
| da1 (min) | 74 mm |
| da2 (min) | 70 mm |
| Da1 (max) | 111 mm |
| Da2 (max) | 114.6 mm |
| ra (max) | 1.5 mm |
| ra1 (max) | 1 mm |