

Toyana 3818-2RS angular contact ball bearings

Toyana 3818-2RS angular contact ball bearings with easy-to-use parts graphics, 2-15/16 in Shaft Size giving you the Mounted Bearing Engineering Group ability to check parts availability, pricing, examine remanufactured options.

| | |
|-------------------------|-------------------------|
| Engineering Group | Mounted Bearing |
| Shaft Size | 2-15/16 in |
| Shaft Size Type | Imperial |
| Full Timken Part Number | QVVF17V215SB |
| Locking Style | Double V-Lock |
| Weight | 30 lb |
| Housing Style | Four-Bolt Square Flange |
| UPC Code | 0883450209816 |
| Dimension BC | 9.45 in |
| Dimension A | 11.12 in |
| Dimension C | 4.19 in |
| Dimension D | 7.480 in |
| Dimension E | 6.68 in |
| Dimension F | 8.35 in |
| Dimension H | 1.00 in |
| Dimension J (Bolt Size) | 0.625 in |
| Dimension G | 1 in |
| Dimension L | 3.3 in |
| Dimension N | 2.7500 in |
| Dimension RVV | 0.88 in |
| Dimension SVV | 4.18 in |

| | |
|-------------------------------------|-----------|
| C – Dynamic Load (Basic) | 66900 lb |
| C0 – Static Load | 71900 lb |
| e – Geometry Factor | 0.23 |
| Y1 – Geometry Factor | 2.90 |
| Y2 – Geometry Factor | 4.31 |
| Oil Lubrication – M/N Seal | 1400 rpm |
| Oil Lubrication – T Seal | 2400 rpm |
| Oil Lubrication – B/C/O Seal | 1100 rpm |
| Grease Lubrication – M/N Seal | 1400 rpm |
| Grease Lubrication – T Seal | 2000 rpm |
| Grease Lubrication – B/C/O Seal | 1100 rpm |
| Float | 0.083 in |
| Shaft Tolerance | 0.0020 in |
| Eng Internal Radial Clearance – Min | 0.0037 |
| Eng Internal Radial Clearance – Max | 0.0047 |
| Pre Install Clearance Min | 0.0037 in |
| Pre Install Clearance Max | 0.0047 in |