

# Toyana 7011 A-UX angular contact ball bearings

Welcome 0.0 Inventory to the TIMKEN Manufacturer Name Toyana 7011 A-UX angular contact ball bearings online N/A Minimum Buy Quantity seller.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 15.89  |
| EAN                       | 0883450995047  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | Concentric Collar  |
| Housing Style             | 4 Bolt Square Flange Block   |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Expansion  |
| Mounting Bolts            | 3/4 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22218  |
| Seals                     | Double Lip Viton   |
| Housing Configuration     | 1 Piece Solid  |
| Pilot Configuration       | With Pilot   |
| Inch – Metric             | Inch   |
| Long Description          | 4 Bolt Square Flange Block;<br>3-1/2" Bore; 9-1/2" Bolt<br>Circle; 6.72" Bolt Spacing; 1<br>Pi |

|                                       |   |
|---------------------------------------|---|
| Other Features                        | Double Row   Single Collar   With Set Screw |
| UNSPSC                                | 31171501                                    |
| Harmonized Tariff Code                | 8483.20.40.80                               |
| Noun                                  | Bearing                                     |
| Keyword String                        | Flanged                                     |
| Manufacturer Item Number              | QAFLP18A308SEC                              |
| Weight / LBS                          | 35  |
| Nominal Bolt Circle Diameter<br>Round | 9.5 Inch   241 Millimeter                   |
| Bolt Spacing                          | 6.72 Inch   170.7 Millimeter                |
| D                                     | 4.03 Inch   102.362 Millimeter              |
| Cartridge Pilot Diameter              | 7.375 Inch   187.32 Millimeter              |
| Cartridge Pilot Depth                 | 0.188 Inch   4.775 Millimeter               |
| d                                     | 3.5 Inch   88.9 Millimeter                  |