

# Toyana 7012 A-U0 angular contact ball bearings

Welcome to the 69.85 mm da Toyana 7012 A-U0 angular contact ball bearings 140 mm Da online seller.

|                         |              |
|-------------------------|--------------|
| da                      | 69.85 mm     |
| Da                      | 140 mm       |
| Ca                      | 42.799 mm    |
| A1                      | 88.9 mm      |
| A2                      | 126.603 mm   |
| S                       | 4.763 mm     |
| ba                      | 34.131 mm    |
| H                       | 169.863 mm   |
| H1                      | 88.9 mm      |
| H2                      | 31.75 mm     |
| J min.                  | 244.475 mm   |
| J max.                  | 279.4 mm     |
| L                       | 330.2 mm     |
| N1                      | 22.225 mm    |
| R1                      | 53.181 mm    |
| R2                      | 21.431 mm    |
| RG                      | 3/8 NPT      |
| PG                      | 1/8 NPT      |
| h                       | 31.75 mm     |
| Housing                 | SAF 516      |
| Bearing                 | 22216 EK     |
| Adapter sleeve assembly | SNW 16×2.3/4 |
| Stabilizing ring        | SR-16-13     |

|  |                |
|--|----------------|
| Labyrinth ring                         | 2 x LOR 45     |
| PosiTrac Plus contact element          | 2 x B10724-44  |
| End plug (suffix Y)                    | EPR 8          |
| Max. speed for PosiTrac Plus seal      | 2150 r/min     |
| P60°                                   | 83.2 kN        |
| P90°                                   | 49.8 kN        |
| P120°                                  | 30.2 kN        |
| P150°                                  | 26.7 kN        |
| P180°                                  | 31.6 kN        |
| Pa                                     | 7.83 kN        |
| Mass pillow block                      | 16.3 kg        |
| Cap bolt                               | 2 x 5/8-11 UNC |
| Cap bolt recommended tightening torque | 149.1 N·m      |
| Cap bolt, SAE grade                    | 5              |
| Appropriate attachment bolt size G     | 0.75 in        |
| Initial grease fill                    | 87.885 g       |