

Toyana 7034 B-UX angular contact ball bearings

Toyana 7034 B-UX angular contact ball bearings Industries and Applications ? We sell discount 35 mm d online as well as cheap machinery parts.

d	35 mm
D	80 mm
B	21 mm
C	18 mm
T	22.75 mm
d1	55.5 mm
a	17 mm
rs min	2 mm
r1s min	1.5 mm
e	0.31
Y2	1.9
Y0	1.05
Mass	0.54 kg
ISO 355 reference	T2FB035
Dynamic load, C	75 kN
Rating life coefficient, A2	1
Static load, C0	77 kN
Fatigue limit load, Cu	9.4 kN
Nlim (oil)	6,600 rpm
Nlim (grease)	5,000 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C

Characteristic cage frequency, FTF	0.4 Hz
Characteristic rolling element frequency, BSF	4.71 Hz
Characteristic outer ring frequency, BPF0	5.6 Hz
Characteristic inner ring frequency, BRFI	8.4 Hz
da max	45 mm
db min	45 mm
Da min	70 mm
Da max	71.5 mm
Db min	74 mm
Ca min	3 mm
Cb min	4.5 mm
ra max	2 mm
r1a max	1.5 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.545
EAN	4547359292626
Product Group	B04334