

Toyana 7040 A-UX angular contact ball bearings

Manufacturers of all are represented in 150 mm da our partial list of clients. Contact Gary 168.275 mm db for a complete Toyana 7040 A-UX angular contact ball bearings list of clients and projects.

da	150 mm
db	168.275 mm
dc	146.05 mm
Da	269.999 mm
Ca	105.816 mm
A1	158.75 mm
A2	279.4 mm
S	4.763 mm
ba	77.787 mm
H	317.5 mm
H1	160.35 mm
H2	63.5 mm
J min.	431.8 mm
J max.	463.55 mm
J1	95.25 mm
L	539.75 mm
N1	28.575 mm
R1	95.25 mm
R2	39.688 mm
RG	3/4 NPT
PG	1/4 NPT

h	50.8 mm
Housing	SAW 230
Bearing	23230 CC/W33
Lock nut	AN 30
Lock washer	W 30
Stabilizing ring	SR-30-0
Taconite seal (db shaft position)	TER 151
Taconite seal (dc shaft position)	TER 134
End plug (suffix Y)	EPR 17
Max. speed for Taconite seal	460 r/min
P60°	230 kN
P90°	138 kN
P120°	87.2 kN
P150°	80.1 kN
P180°	96.1 kN
Pa	43.2 kN
Mass pillow block	92.5 kg
Cap bolt	4 x 3/4-10 UNC
Cap bolt recommended tightening torque	359.3 N·m
Cap bolt, SAE grade	5
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	623.7 g