

Toyana 7206 B-UD angular contact ball bearings

Question Toyana 7206 B-UD angular contact ball bearings ? Find what you need faster 40 Bore Diameter (mm) by entering 40x80x18 Size (mm) your information .

Size (mm)	40x80x18
Bore Diameter (mm)	40
Outer Diameter (mm)	80
Width (mm)	18
d	40 mm
D	80 mm
B	18 mm
C	18 mm
a	3,28 mm
b	2,05 mm
f	1,65 mm
r min.	1,1 mm
r0 max.	0,6 mm
r1 min.	0,5 mm
D1	76,81 mm
D2	86,6 mm
da min.	46,5 mm
Da max.	73,5 mm
Weight	0,366 Kg
Basic dynamic load rating (C)	29,1 kN
Basic static load rating (C0)	17,8 kN
(Grease) Lubrication Speed	8300 r/min

(Oil) Lubrication Speed	10000 r/min
Inventory	0.0
Manufacturer Name	KOYO
Minimum Buy Quantity	N/A
Weight / Kilogram	0.396
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	Yes
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	40MM Bore; 80MM Outside Diameter; 18MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Fil
Other Features	Deep Groove With Snap Ring
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.80689
Bore	1.575 Inch 40 Millimeter
Outer Race Width	0.709 Inch 18 Millimeter
Outside Diameter	3.15 Inch 80 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Bearing No.	6208NR

r(min)	1.1
r1(min)	0.5
Cr	36.4
C0r	17.8
Cu	1.25
f0	14.0
Grease lub.	8300
Oil lub.	10000
D2(min)	86.6
f(ϕ 0.05)	1.65
da(min)	46.5
Da(max)	73.5
Dx(min)	88
Cy(max)	4.67
ra(max)	1
rb(max)	0.5
(Refer.) Mass (kg)	0.366