

Toyana 7234 B-U0 angular contact ball bearings

We work closely with our Toyana 7234 B-U0 angular contact ball bearings manufacturing 30 Bore Diameter (mm) partners to bring 30x72x30.2 Size (mm) the best value to customers.

Size (mm)	30x72x30.2
Bore Diameter (mm)	30
Outer Diameter (mm)	72
Width (mm)	30.2
d	30 mm
D	72 mm
B	30.2 mm
C	30.2 mm
a	3.28 mm
b	1.9 mm
r min.	1.1 mm
D1	68.81 mm
Weight	0.510 Kg
Basic dynamic load rating (C)	41,5 kN
Basic static load rating (C0)	29 kN
(Grease) Lubrication Speed	7000 r/min
Bore Type	Cylindrical Bore
Enclosure	Open
Configuration	Double Row
Bore Size	30 mm
Outside Diameter	72 mm
Width	30.2 mm

Fillet Radius/Chamfer	1.1 mm
Groove Width	1.9 mm
Groove Diameter	68.8 mm
a (max)	3.3 mm
Dynamic Load Rating	41,500 N
Static Load Rating	29,000 N
Limiting Speed – Grease	7,000 rpm
Limiting Speed – Oil	9,500 rpm
Radial Clearance	0.005 to 0.020 mm
da	37 mm
Da	65 mm
Dx	80 mm
ra	1 mm
Cy	4.7 mm