

Toyana 7244 ATBP4 angular contact ball bearings

High Quality Toyana 7244 ATBP4 angular contact ball bearings. Competitive 200x130x33 Size (mm) Pricing. Accept Small Order. Easy and Fast Shipping.

Size (mm)	200x130x33
Bore Diameter (mm)	200
Outer Diameter (mm)	130
Width (mm)	33
d	130 mm
D	200 mm
B	33 mm
d1	152.6 mm
D2	181.4 mm
r1,2 – min.	2 mm
da – min.	139 mm
da – max.	152.9 mm
Da – max.	191 mm
ra – max.	2 mm
Basic dynamic load rating – C	112 kN
Basic static load rating – C0	100 kN
Fatigue load limit – Pu	3.4 kN
Limiting speed	2000 r/min
Calculation factor – kr	0.025
Calculation factor – f0	15.8
Inventory	0.0
Manufacturer Name	SKF

Minimum Buy Quantity	N/A
Weight / Kilogram	3.346
EAN	7316570368901
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	130MM Bore; 200MM Outside Diameter; 33MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; N
Other Features	Deep Groove NBR Seal
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6026-2RS1
Weight / LBS	7.371
Outside Diameter	7.874 Inch 200 Millimeter
Outer Race Width	1.299 Inch 33 Millimeter
Bore	5.118 Inch 130 Millimeter
Inner Race Width	0 Inch 0 Millimeter
bore diameter:	130 mm

static load capacity:	100 kN
outside diameter:	200 mm
finish/coating:	Uncoated
overall width:	33 mm
bearing material:	Steel
bore type:	Round
cage material:	Steel
closure type:	Double Sealed
fillet radius:	2 mm
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm:	2000 rpm
snap ring included:	Without Snap Ring
series:	60
internal clearance:	C0
weight:	7.32 lbs
operating temperature range:	Max 250 °F
manufacturer product page:	Click here
dynamic load capacity:	112 kN
manufacturer upc number:	7316570368901
d1 ≈	152.6 mm
D2 ≈	181.4 mm
r1,2 min.	2 mm
da min.	139 mm
da max.	152.9 mm
Da max.	191 mm
ra max.	2 mm
Basic dynamic load rating C	112 kN
Basic static load rating C0	100 kN
Fatigue load limit Pu	3.35 kN

Calculation factor k_r	0.025
Calculation factor f_0	15.8
Mass bearing	3.32 kg