

# Toyana 7330 C-U0 angular contact ball bearings

Manufacturers of all are represented in our partial list of clients. Contact Gary for a complete 0.0 Inventory Toyana 7330 C-U0 angular contact ball bearings list of clients and projects. N/A Minimum Buy Quantity

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | ABB MOTORS AND MECHANICAL INC                       |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 3.3   |
| EAN                       | 0782475796779                                       |
| Product Group             | M06110  |
| Number of Mounting Holes  | 2   |
| Mounting Method           | Set Screw   |
| Housing Style             | 2 Bolt Pillow Block                                 |
| Rolling Element           | Ball Bearing  |
| Housing Material          | Cast Iron   |
| Expansion / Non-expansion | Non-expansion                                       |
| Mounting Bolts            | 16 Millimeter                                       |
| Relubricatable            | Yes   |
| Insert Part Number        | INS-VSC-50M   |
| Seals                     | Single Lip Contact                                  |
| Housing Configuration     | 1 Piece Solid                                       |
| Inch – Metric             | Metric  |
| Other Features            | Single Row   Intermediate Duty<br>  Wide Inner Race |

|                               |  |
|-------------------------------|--|
| Long Description              | 2 Bolt Pillow Block; 50MM Bore; 57.2MM Base to Center Height; Set Screw Mount; Ball Bearing; 152.4MM |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.40  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Manufacturer Item Number      | P2B-VSC-50M  |
| Manufacturer Internal Number  | 125692   |
| Weight / LBS                  | 7.275  |
| Nominal Bolt Center to Center | 6.3 Inch   160 Millimeter  |
| D                             | 1.626 Inch   41.3 Millimeter   |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter   |
| Bolt Spacing Maximum          | 6.689 Inch   169.9Millimeter   |
| Bolt Spacing Minimum          | 6 Inch   152.4Millimeter   |
| d                             | 1.969 Inch   50 Millimeter   |
| B                             | 2.252 Inch   57.2 Millimeter   |