

Toyana CRF-42.343016 wheel bearings

Toyana CRF-42.343016 wheel bearings Manufacturers 17x47x14 Size (mm) , Online Wholesale Suppliers 47 Outer Diameter (mm) !

Size (mm)	17x47x14
Bore Diameter (mm)	17
Outer Diameter (mm)	47
Width (mm)	14
d	17 mm
D	47 mm
B	14 mm
C	14 mm
Angle (α)	40 °
a	20,5 mm
r min.	1 mm
r1 min.	0,6 mm
da min.	22,5 mm
db min	21,5 mm
ra max.	1 mm
Weight	0,109 Kg
Basic dynamic load rating (C)	14,8 kN
Basic static load rating (C0)	8 kN
(Grease) Lubrication Speed	15 000 r/min
Contact angle α	40 °
rs min	1 mm
r1s min	0.6 mm

Mass	0.11 kg
Dynamic load, C	14.8 kN
Static load, C0	8 kN
Fatigue limit load, Cu	0.36 kN
Nlim (oil)	20,000 rpm
Nlim (grease)	15,000 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
da min	22.5 mm
Da max	41.5 mm
Db max	42.5 mm
r1a max	0.6 mm
ra max	0.6 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.116
EAN	4547359448160
Product Group	B00308
Enclosure	Open
Flush Ground	No
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Steel
Contact Angle	40 Degree
Internal Clearance	C0-Medium

Number of Bearings	1 (Single)
Inch – Metric	Metric
Long Description	17MM Bore; 47MM Outside Diameter; 14MM Width; Open; No Flush Ground; Ball Bearing; Single Row of Bal
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer Item Number	7303B
Weight / LBS	0.256
Bore	0.669 Inch 17 Millimeter
Width	0.551 Inch 14 Millimeter
Outside Diameter	1.85 Inch 47 Millimeter
bore diameter:	17 mm
radial static load capacity:	8000 N
outside diameter:	47 mm
operating temperature range:	-40 to 120 °C
overall width:	14 mm
cage material:	Steel
contact angle:	40 °
maximum rpm:	20000 rpm
row type & fill slot:	Single-Row Non-Fill Slot
finish/coating:	Uncoated
bore type:	Round
precision rating:	ISO Class 0
closure type:	Open
fillet radius:	1 mm
snap ring included:	Without Snap Ring

weight:	0.116 kg
bearing material:	High Carbon Chrome Steel
manufacturer product page:	Click here
radial dynamic load capacity:	14800 N