

Toyana CX484 wheel bearings

Various Mounted Bearing Engineering Group types and sizes to accommodate your Toyana CX484 wheel bearings requirements.

| | |
|--------------------------|-----------------------|
| Engineering Group | Mounted Bearing |
| Shaft Size | 70 mm |
| Shaft Size Type | Metric |
| Full Timken Part Number | QMPL15J070SB |
| Locking Style | Eccentric |
| Weight | 28 lb |
| Housing Style | Two-Bolt Pillow Block |
| UPC Code | 0883450087728 |
| Dimension A | 3.25 in |
| Dimension B | 6.59 in |
| Dimension C | 4.01 in |
| Dimension D Max | 8.40 in |
| Dimension D Min | 7.70 in |
| Dimension F | 10.44 in |
| Dimension G | 3.0000 in |
| Dimension H | 1.38 in |
| Dimension J (Bolt Size) | 0.750 in |
| Dimension K | 1.25 in |
| Dimension L | 3.87 in |
| Dimension M | 2.37 in |
| Dimension R | 0.25 in |
| Dimension S | 3.62 in |
| C0 – Static Load | 54100 lb |
| C – Dynamic Load (Basic) | 49900 lb |

| | |
|-------------------------------------|-----------|
| e – Geometry Factor | 0.22 |
| Y1 – Geometry Factor | 3.14 |
| Y2 – Geometry Factor | 4.67 |
| Oil Lubrication – M/N Seal | 1600 rpm |
| Oil Lubrication – T Seal | 2900 rpm |
| Oil Lubrication – B/C/O Seal | 1300 rpm |
| Grease Lubrication – M/N Seal | 1600 rpm |
| Grease Lubrication – T Seal | 2400 rpm |
| Grease Lubrication – B/C/O Seal | 1300 rpm |
| Float | 0.083 in |
| Shaft Tolerance | 0.0020 in |
| Eng Internal Radial Clearance – Min | 0.0020 |
| Eng Internal Radial Clearance – Max | 0.0031 |
| Pre Install Clearance Min | 0.0020 in |
| Pre Install Clearance Max | 0.0031 in |