

# Toyana H238148/10 tapered roller bearings

YOU'LL FIND AN EXTENSIVE SELECTION 125x70x31 Size (mm) OF Toyana H238148/10 tapered roller bearings FOR 70 Outer Diameter (mm) SALE.

Size (mm)	125x70x31
Bore Diameter (mm)	125
Outer Diameter (mm)	70
Width (mm)	31
d	70 mm
D	125 mm
B	31 mm
d1	89.4 mm
D1	108.2 mm
F	83.5 mm
r1,2 – min.	1.5 mm
r3,4 – min.	1.5 mm
s	1.7 mm
da – min.	79 mm
da – max.	81 mm
db – min.	92 mm
Da – max.	115.4 mm
ra – max.	1.5 mm
Basic dynamic load rating – C	180 kN
Basic static load rating – C0	193 kN
Fatigue load limit – Pu	25.5 kN
Reference speed	6000 r/min

Limiting speed	6300 r/min
Calculation factor – kr	0.2
d1 ≈	89.4 mm
D1 ≈	108.2 mm
r1,2 min.	1.5 mm
r3,4 min.	1.5 mm
s max.	1.7 mm
da min.	79 mm
da max.	81 mm
db min.	92 mm
Da max.	115.4 mm
ra max.	1.5 mm
Basic dynamic load rating C	180 kN
Basic static load rating C0	193 kN
Fatigue load limit Pu	25.5 kN
Calculation factor kr	0.2
Limiting value e	0.3
Axial load factor Y	0.4
Mass bearing	1.73 kg
Angle ring	HJ 2214 EC