

Toyana NA4830 needle roller bearings

Our highly-skilled and factory-trained service experts have the 16 Outer Diameter (mm) resources to help you with all your Toyana NA4830 needle roller bearings needs – including routine maintenance, major repairs, warranty 6x16x28 Size (mm) service, and equipment inspections.

Size (mm)	6x16x28
Bore Diameter (mm)	6
Outer Diameter (mm)	16
Width (mm)	28
D	16 mm
d	6 mm
B	28 mm
C	11 mm
B1	16 mm
C1	0.6 mm
d1	12.5 mm
G	M 6
G1	8 mm
SW	4 mm
r1,2 – min.	0.15 mm
Basic dynamic load rating – C	3.1 kN
Basic static load rating – C0	3.2 kN
Fatigue load limit – Pu	0.345 kN
Maximum dynamic radial loads – Fr	2.9 kN
Maximum static radial loads – F0r	4.2 kN

Limiting speed	6000 r/min
Mass support roller	0.019 kg
Recommended tightening torque	3 N·m
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.02
EAN	7316571594446
Product Group	B04144
Roller Surface Profile	Crowned
Profile	Stud Type
Thread Size	M6X1
Stud Profile	Standard Stud
Enclosure	Sealed
Rolling Element	Needle Bearing
Relubricatable	No
Hex Socket	Yes
Inch – Metric	Metric
Other Features	Caged Polyamide 66 Axial Sliding 3 Stage Sealing
Long Description	16MM Roller Diameter; 11MM Roller Width; Crowned Roller Surface; Stud Type; 6MM Stud Diameter; M6X1
UNSPSC	31171530
Harmonized Tariff Code	8482.40.00.00
Noun	Bearing
Keyword String	Cam Follower
Manufacturer Item Number	KR 16 PPSKA
Weight / LBS	0.04

Stud Diameter	0.236 Inch 6 Millimeter
Roller Diameter	0.63 Inch 16 Millimeter
Roller Width	0.433 Inch 11 Millimeter
r _{1,2} min.	0.15 mm
Basic dynamic load rating C	3.14 kN
Basic static load rating C ₀	3.2 kN
Fatigue load limit P _u	0.345 kN
Maximum dynamic radial loads F _r max.	2.9 kN
Maximum static radial loads F _{0r} max.	4.15 kN
Mass cam follower	0.019 kg
Hexagonal nut	M 6×1