

Toyana NA6915-2RS needle roller bearings

Various types 101.6 mm da and sizes to accommodate your Toyana NA6915-2RS needle roller bearings requirements.

da	101.6 mm
Da	200 mm
Ca	62.789 mm
A1	120.65 mm
A2	165.1 mm
S	4.763 mm
ba	50.006 mm
H	239.316 mm
H1	125.425 mm
H2	50.8 mm
J min.	320.675 mm
J max.	368.3 mm
J1	69.85 mm
L	419.1 mm
N1	22.225 mm
R1	67.866 mm
R2	31.75 mm
RG	3/8 NPT
PG	1/4 NPT
h	45.244 mm
Housing	SAF 522
Bearing	22222 EK
Adapter sleeve assembly	SNW 22×4

Stabilizing ring	SR-22-19
Labyrinth ring	2 x LOR 110
End plug (suffix Y)	EPR 13
Bearing limiting speed	4000 r/min
P60°	149 kN
P90°	89 kN
P120°	55.6 kN
P150°	50.7 kN
P180°	60.9 kN
Pa	17.3 kN
Mass pillow block	33.1 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N·m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.75 in
Initial grease fill	232.47 g