

Toyana NH2308 E cylindrical roller bearings

What are the types of 130 Bore Diameter (mm) Toyana NH2308 E cylindrical roller bearings ? Manufacturing Service . 130x60x33.5 Size (mm) Get Your Free, Instant price, design review.

Size (mm)	130x60x33.5
Bore Diameter (mm)	130
Outer Diameter (mm)	60
Width (mm)	33,5
d	60 mm
D	130 mm
T	33.5 mm
d1	96 mm
B	31 mm
C	22 mm
r1,2 – min.	3 mm
r3,4 – min.	2.5 mm
a	39 mm
da – max.	73 mm
db – min.	72 mm
Da – min.	103 mm
Da – max.	118 mm
Db – min.	123 mm
Ca – min.	2 mm
Cb – min.	11.5 mm
ra – max.	3 mm

rb – max.	2.5 mm
Basic dynamic load rating – C	145 kN
Basic static load rating – C0	166 kN
Fatigue load limit – Pu	20.4 kN
Reference speed	3600 r/min
Limiting speed	5300 r/min
Calculation factor – e	0.83
Calculation factor – Y	0.72
Calculation factor – Y0	0.4
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	1.962
EAN	7316570003093
Product Group	B04334
bore diameter:	60 mm
operating temperature range:	Maximum of +250 °F
cup width:	22 mm
dynamic load capacity:	145 kN
assembly type:	Cone & Cup
static load capacity:	166 kN
outside diameter:	130 mm
finish/coating:	Uncoated
cone width:	31 mm
maximum rpm:	5300 RPM
closure type:	Open
series:	313
cage material:	Steel
flange type:	Non-Flanged Cup