

# Toyana NJ2084 cylindrical roller bearings

Welcome to N/A Minimum Buy Quantity the Toyana NJ2084 cylindrical roller bearings 0.0 Inventory REXNORD Manufacturer Name online seller.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | REXNORD  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 27.24  |
| EAN                       | 0698210894306  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | Concentric Collar  |
| Housing Style             | 4 Bolt Round Flange Cartridge  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 3/4 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 5315U  |
| Seals                     | Heavy Contact  |
| Housing Configuration     | 1 Piece Solid  |
| Pilot Configuration       | With Pilot   |
| Inch – Metric             | Inch   |
| Long Description          | 4 Bolt Round Flange Cartridge;<br>3-15/16" Bore; 9.4" Bolt<br>Circle; 6-5/8" Bolt Spacing; |

|                                       |   |
|---------------------------------------|---|
| Other Features                        | Double Row   Double Collar  <br>Open Auxiliary End Cap<br>Threaded Cover Side   With Set<br>Screw |
| UNSPSC                                | 31171501  |
| Harmonized Tariff Code                | 8483.20.40.80   |
| Noun                                  | Bearing   |
| Keyword String                        | Flanged   |
| Manufacturer Item Number              | MBR5315A66  |
| Manufacturer Internal Number          | 6889430   |
| Weight / LBS                          | 53  |
| Nominal Bolt Circle Diameter<br>Round | 9.4 Inch   238 Millimeter   |
| d                                     | 3.938 Inch   100.025<br>Millimeter  |
| D                                     | 6.25 Inch   158.75 Millimeter   |
| Cartridge Pilot Diameter              | 8.125 Inch   206.375<br>Millimeter  |
| Bolt Spacing                          | 6.625 Inch   168.275<br>Millimeter  |
| Cartridge Pilot Depth                 | 1.5 Inch   38.1 Millimeter  |