

# Toyana NK5/12 needle roller bearings

Toyana NK5/12 needle roller bearings Industries and Applications ? We sell 50×51.66×54 Size (mm) discount online as well as cheap machinery parts.

Size (mm)	50×51.66×54
Bore Diameter (mm)	50
Outer Diameter (mm)	51,66
Width (mm)	54
d	51.66 mm
A	54 mm
A1	34 mm
A5	29.5 mm
B1	46 mm
H	26 mm
H1	57.2 mm
H2	22 mm
J	157 mm
J – max.	165 mm
J – min.	149 mm
L	203 mm
N1	18 mm
s1	27.5 mm
J6	187 mm
J7	19 mm
N4	4 mm
DN	6.5 mm

SWN	7 mm
GN – 1/4-28 SAE-LT	1/428 SAELT
RG – 1/4-28 UNF	1/428 UNF
R1	4 mm
Rα	45 °
Basic dynamic load rating – C	35.1 kN
Basic static load rating – C0	23.2 kN
Fatigue load limit – Pu	0.98 kN
Limiting speed	4000 r/min
Weight	2.65 kg
Hexagonal key size for grub screw – H	3 mm
Recommended tightening torque for grub screw	7.4 N·m
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	2.61
EAN	7316574719006
Product Group	M06110
Housing material	Cast iron
J max.	165 mm
J min.	149 mm
N	26 mm
RG	1/4-28 UNF
Rα	45 °
GN	1/4-28 SAE-LT
Basic dynamic load rating C	35.1 kN
Basic static load rating C0	23.2 kN
Fatigue load limit Pu	0.98 kN
Mass bearing unit	2.65 kg

Thread grub screw G2	M6
Hexagonal key size for grub screw N	3 mm
Recommended diameter for attachment bolts, mm G	16 mm
Recommended diameter for attachment bolts, inch G	0.625 in
Housing	SY 510 M
Bearing	YSP 210 SB-2F
End cover	ECY 210