

Toyana NKI6/12 needle roller bearings

100% Authentic. 75 Bore Diameter (mm) Toyana NKI6/12 needle roller bearings 75x160x58 Size (mm) Highest Quality. Certified Supplier.

Size (mm)	75x160x58
Bore Diameter (mm)	75
Outer Diameter (mm)	160
Width (mm)	58
d	75 mm
D	160 mm
T	58 mm
B	55 mm
C	45 mm
a	40 mm
r min.	3 mm
r2 min.	2,5 mm
da min.	89 mm
da max	91 mm
Da min	133 mm
Da max.	148 mm
Db min.	149 mm
ra max.	2,5 mm
rb max.	2 mm
Weight	5,41 Kg
Basic dynamic load rating (C)	363 kN
Basic static load rating (C0)	481 kN

(Grease) Lubrication Speed	2500 r/min
(Oil) Lubrication Speed	3300 r/min
Calculation factor (e)	0,35
Calculation factor (Y0)	0,96
Inventory	0.0
Manufacturer Name	KOYO
Minimum Buy Quantity	N/A
Weight / Kilogram	5.42
EAN	0605790022302
Product Group	B04334
Precision Class	Standard
Component	Assembly
Basic Number	32315
Number of Tapered Rows	Single Row
Inch – Metric	Metric
Other Features	High Load Capacity
Long Description	Assembly; Standard Precision; 75MM Bore; 160MM Outside Diameter; 58MM Assembly Width; Single Row of
UNSPSC	31171516
Harmonized Tariff Code	8482.20.00.00
Noun	Bearing
Keyword String	Tapered
Manufacturer Item Number	32315JR
Weight / LBS	11.927
Flange Outside Diameter	0 Inch 0 Millimeter
Assembly Width	2.283 Inch 58 Millimeter
Bore	2.953 Inch 75 Millimeter
Outside Diameter	6.299 Inch 160 Millimeter

Bearing No.	32315JR
r(min)	3
r1(min)	2.5
Cr	454
C0r	481
Cu	64.6
Grease lub.	2500
Oil lub.	3300
a(mm)	40.0
da(min)	89
db(max)	91
Da(max)	148
Da(min)	133
Db(min)	149
Sa(min)	4
Sb(min)	13
ra(max)	2.5
rb(max)	2
e	0.35
Y1	1.74
Y0	0.96
(Refer.) Mass (kg)	5.41