

# Toyana NNU4934 cylindrical roller bearings

Our highly-skilled and factory-trained service experts have the resources to help you with all N/A Minimum Buy Quantity your Toyana NNU4934 cylindrical roller bearings needs – including routine maintenance, 0.0 Inventory major repairs, warranty service, and equipment inspections.

|                           |                          |
|---------------------------|--------------------------|
| Inventory                 | 0.0                      |
| Manufacturer Name         | TIMKEN                   |
| Minimum Buy Quantity      | N/A                      |
| Weight                    | 106.69                   |
| EAN                       | 0883450373678            |
| Product Group             | M06288                   |
| Number of Mounting Holes  | 4                        |
| Mounting Method           | V Lock                   |
| Housing Style             | 4 Bolt Pillow Block      |
| Rolling Element           | Spherical Roller Bearing |
| Housing Material          | Cast Steel               |
| Expansion / Non-expansion | Expansion                |
| Mounting Bolts            | 24 Millimeter            |
| Relubricatable            | Yes                      |
| Insert Part Number        | 22228                    |
| Seals                     | Double Lip Viton         |
| Housing Configuration     | 1 Piece Solid            |
| Inch – Metric             | Metric                   |
| Other Features            | Double Row   Double Nut  |

|                               |  |
|-------------------------------|--|
| Long Description              | 4 Bolt Pillow Block; 130MM Bore; 155.6MM Base to Center Height; V Lock Mount; Spherical Roller Beari |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.80  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Manufacturer Item Number      | QVVPX28V130SEC   |
| Weight / LBS                  | 136  |
| d                             | 5.118 Inch   130 Millimeter  |
| Bolt Spacing Minimum          | 15.252 Inch   387.4Millimeter  |
| D                             | 7.02 Inch   178.3 Millimeter   |
| Nominal Bolt Center to Center | 16.5 Inch   420 Millimeter   |
| Bolt Spacing Maximum          | 17.815 Inch   452.5Millimeter  |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter   |
| B                             | 6.126 Inch   155.6 Millimeter  |