

Toyana NU2304 E cylindrical roller bearings

Welcome 30 Bore Diameter (mm) to the Toyana NU2304 E cylindrical roller bearings 30x37x4 Size (mm) online seller.

Size (mm)	30x37x4
Bore Diameter (mm)	30
Outer Diameter (mm)	37
Width (mm)	4
d	30 mm
D	37 mm
B	4 mm
C	4 mm
r min.	0,2 mm
da min.	31,6 mm
da max	32,3 mm
Da max.	35,4 mm
ra max.	0,2 mm
Weight	0,006 Kg
Basic dynamic load rating (C)	1,14 kN
Basic static load rating (C0)	0,95 kN
(Grease) Lubrication Speed	3 300 r/min
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.008
EAN	4547359584806
Product Group	B00308

Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Non-Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	30MM Bore; 37MM Outside Diameter; 4MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No F
Other Features	Deep Groove
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6706LLF
Outside Diameter	1.457 Inch 37 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Bore	1.181 Inch 30 Millimeter
Outer Race Width	0.157 Inch 4 Millimeter
bore diameter:	30 mm
static load capacity:	950 N
outside diameter:	37 mm
precision rating:	ISO Class 0
overall width:	4 mm
finish/coating:	Uncoated

bore type:	Round
bearing material:	High Carbon Chrome Steel
closure type:	Double Sealed
cage material:	Stainless Steel
row type & fill slot:	Single Row Non-Fill Slot
inner ring width:	4 mm
snap ring included:	Without Snap Ring
outer ring width:	4 mm
internal clearance:	CN
maximum rpm (grease):	3300 rpm
operating temperature range:	-40 to 140 °C
fillet radius:	0.2 mm
dynamic load capacity:	1140 N
manufacturer product page:	Click here